



# **FOURMI Project:**

# SMART PAINTS STRIPPING for DUAL AERONAUTICS APPLICATIONS

José ALCORTA, RESCOLL j.a@rescoll.fr



# **FOURMI: Thermal Stripping Technology**



- Stripping operations (State of Art):
  - Time consuming (several days eg 12 full days with 20 people for a Boeing 777)
  - EHS issues (solvents + wastes)


# Need for a Quicker and Safer stripping process

### **FOURMI's Stripping Concept**

- 1. Modification of the paint system
- 2. Coating of the aircraft (after traditionnal stripping)
- 3. Service
- 4. Stripping triggered by a thermal activation
- 5. Clean removal of the solid wastes, without solvents

#### Benefits:

- Quicker => low cost
- Safer for operators
- Less impactant on Environment regarding chemical wastes







- Fuselage stripping : Specifications
  - Same adhesion and ageing performance after paint modification
  - Same aesthetic performance

#### **Case Study 1: Military Aircraft**

PU Topcoat

Epoxy primer

Composite

Thermal Stripping

Target stripping T: 130°C

Selective stripping of the topcoat

Epoxy primer

Composite

#### Case Study 2: Civil Aircraft

PU Topcoat

Sandable primer

Epoxy primer

Cr Epoxy primer

CAA

Aluminium

Thermal Stripping

Target stripping T: 130°C

Selective stripping of the topcoat & sandable primer

Epoxy primer
Cr Epoxy primer
CAA
Aluminium

CONFIDENTIEL RESCOLL © 2017






Fuselage stripping : Results

#### **Case Study 1: Military Aircraft**

- 100x100mm sample, stripped in less than 1 min
- Selective removal of the topcoat
- 100% solid wastes
- Easy recovering of the clean and non-damaged epoxy primer (pale yellow)

#### **Case Study 2: Civil Aircraft**

- Samples, stripped in less than 1 min
- Selective removal of the topcoat + sandable primer
- 100% solid wastes
- Easy recovering of the clean and nondamaged epoxy primer (pale yellow)







Fuselage stripping : Results

#### **Ageing of FOURMI Paint System (Immersion tests)**

Condition	Configuration	Result (ISO 2409)
Water 14days @ 23°C	Military and Civil	<ul> <li>GTO initial</li> <li>GTO-1 after ageing</li> <li>Stripping capability given after ageing</li> </ul>
Hydraulic Fluid 14d @ 23°C		
Toluene 25%, trimethylpentane 75% 2h @ 23°C		
Kerozene 7d @ 23°C		
De-icing fluid 7d @ 23°C		

Repainting and re-stripping also proven





# FOURMI Project - Next Stages

- Aeronautical paint Manufacturer X:
- Prospecting for a civil aviation application
- Prospecting for a military naval application
- Samples supplied to Prospects under NDA, 1st stability tests (including UV) are encouraging; delamination tests underway (technology commissioning by Prospects)
  - AIRBUS:
- Evaluation of the technology for different paint applications (underway)